Rotoplat 508 DW

Semi-Automatic Door & Window Turntable Stretch Wrapping Machine



Technical Features	
Turntable Diameter	65"
Maximum Load Weight	220 lbs
Load Height	41.5"-110"
Roll Carriage	Power Dual Stretch (PDS)
Turntable Rotation	5-12 RPM
Roll Carriage Speed	5-18 ft/min
Power Supply	110VAC

The Rotoplat 508 DW is equipped with a large 65" diameter turntable and a unique clamping top platen that allow for wrapping doors and windows.

The 508 DW is capable of wrapping items with a thickness of 1.5" to 14" thick; 30" to 70" wide; and 42" to 110" high.

Adjustable brackets allow you to wrap different sizes, based on your needs.

The Power Dual Pre-Stretch Roll Carriage System (PDS) delivers 250% pre-stretch using fixed gears. By activating the "Double Stretch" control, the carriage can switch to variable pre-stretch via a clutch positioned on the first roller.

Containment force is also adjustable from the coor touchscreen operator control panel. Robopac's patented high-performance S-Wrap Pattern (with Quick Load System) and load cell compensation and containment force give you total film control.

A foot pedal controls the top platen, allowing the operator to hold the door in place, while lowering the clamp to secure the product.

The optional Pluripac delivery system applies foam/bubble wrap material at the same time as the stretch film to provide additional protection.

